

Package: fusionclust (via r-universe)

September 22, 2026

Title Clustering and Feature Screening using L1 Fusion Penalty

Version 1.0.0

Description Provides the Big Merge Tracker and COSCI algorithms for convex clustering and feature screening using L1 fusion penalty.

Depends R ($\geq 3.4.1$)

License GPL(≥ 2)

Encoding UTF-8

LazyData true

Imports bbmle, stats, graphics

RoxygenNote 6.0.1

URL <https://github.com/trambakbanerjee/fusionclust>

Suggests knitr, rmarkdown

VignetteBuilder knitr

Repository <https://trambakbanerjee.r-universe.dev>

Date/Publication 2021-06-17 21:56:56 UTC

RemoteUrl <https://github.com/trambakbanerjee/fusionclust>

RemoteRef HEAD

RemoteSha 8b6d438ece9f8bb2864ba039e7f2a283100aba02

Contents

bmt	2
cosci_is	3
cosci_is_select	4
nclust	5

Index	7
-------	---

bmt

*Big Merge Tracker***Description**

Solves an L1 relaxed univariate clustering criterion and returns a sequence of λ values where the clusters merge

Usage

```
bmt(x, alpha = 0.1, small.perturbation = 10^(-6))
```

Arguments

x	observation vector
alpha	merging threshold. Default is 0.1
small.perturbation	a small positive number to remove ties. Default is 10^{-6}

Details

solves a convex relaxation of the univariate clustering criterion given by equation (2) in the referenced paper and generates a sequence of cluster merges and corresponding λ values. See algorithm 1 in the referenced paper for more details.

Value

1. path - number of clusters on the big merge path
2. lambda.path - sequence of lambda where clusters merge
3. index - cluster index at the point where clusters merge
4. merge - merge points
5. split - split points
6. prob - merging proportion
7. boundaries - cluster boundaries

References

1. P. Radchenko, G. Mukherjee, Convex clustering via l1 fusion penalization, J. Roy. Statist. Soc. Ser. B (Statistical Methodology) (2017) doi:10.1111/rssb.12226.

See Also

[nclust](#)

Examples

```
library(fusionclust)
set.seed(42)
x<- c(rnorm(1000,-2,1), rnorm(1000,2,1))
out<- bmt(x)
```

cosci_is

*Rank the p features in an n by p design matrix***Description**

Ranks the p features in an n by p design matrix where n represents the sample size and p is the number of features.

Usage

```
cosci_is(dat, min.alpha, small.perturbation = 10^(-6))
```

Arguments

dat	n by p data matrix
min.alpha	the smallest threshold (typically set to 0)
small.perturbation	a small positive number to remove ties. Default value is 10^{-6}

Details

Uses the univariate merging algorithm [bmt](#) and produces a score for each feature that reflects its relative importance for clustering.

Value

a p vector of scores

References

1. Banerjee, T., Mukherjee, G. and Radchenko P., Feature Screening in Large Scale Cluster Analysis, Journal of Multivariate Analysis, Volume 161, 2017, Pages 191-212
2. P. Radchenko, G. Mukherjee, Convex clustering via l1 fusion penalization, J. Roy. Statist. Soc. Ser. B (Statistical Methodology) (2017) doi:10.1111/rssb.12226.

See Also

[bmt](#), [cosci_is_select](#)

Examples

```
library(fusionclust)
set.seed(42)
noise<-matrix(rnorm(49000),nrow=1000,ncol=49)
set.seed(42)
signal<-c(rnorm(500,-1.5,1),rnorm(500,1.5,1))
x<-cbind(signal,noise)
scores<- cosci_is(x,0)
```

cosci_is_select	<i>Use a data driven approach to select the features</i>
-----------------	--

Description

Once you have the feature scores from `cosci_is`, you can select the features

1. based on a pre-defined threshold,
2. using table A.10 in the paper[1] to determine an appropriate threshold or,
3. using a data driven approach described in the references to select the features and obtain an implicit threshold value.

`cosci_is_select` implements option 3.

Usage

```
cosci_is_select(score, gamma)
```

Arguments

score	a p vector of scores
gamma	what proportion of the p features is noise? If your sample size n is smaller than 100, setting gamma = 0.85 is recommended. Otherwise set gamma = 0.9

Details

Converts the problem of screening out features with lower scores into a problem in large scale multiple testing and uses the procedure described in reference [2] to determine the signal features.

Value

a vector of selected features

References

1. Banerjee, T., Mukherjee, G. and Radchenko P., Feature Screening in Large Scale Cluster Analysis, Journal of Multivariate Analysis, Volume 161, 2017, Pages 191-212
2. T. Cai, W. Sun, W., Optimal screening and discovery of sparse signals with applications to multistage high throughput studies, J. Roy. Statist. Soc. Ser. B (Statistical Methodology) 79, no. 1 (2017) 197-223

See Also[cosci_is](#)**Examples**

```
library(fusionclust)
set.seed(42)
noise<-matrix(rnorm(49000),nrow=1000,ncol=49)
set.seed(42)
signal<-c(rnorm(500,-1.5,1),rnorm(500,1.5,1))
x<-cbind(signal,noise)
scores<- cosci_is(x,0)
features<-cosci_is_select(scores,0.9)
```

nclust	<i>No.of clusters</i>
--------	-----------------------

Description

Estimates the number of clusters from the [bmt](#) run

Usage

```
nclust(bmt_output, prob_threshold = 0.5)
```

Arguments

bmt_output output from the [bmt](#) run

prob_threshold probability threshold. Default is 0.5. Do not change it unless you know what you are doing. See the referenced paper

Details

Estimates the number of clusters as the number of big merges + 1. The probability threshold is an adjustment that renders this estimation process more robust to sampling fluctuations. If the sum of the sample frequencies for the two merging clusters in the last big merge is less than 50 percent, we do not report any merges and thus are left with just 1 cluster. See the referenced paper for more details.

Value

The number of clusters

References

1. P. Radchenko, G. Mukherjee, Convex clustering via l1 fusion penalization, J. Roy. Statist. Soc. Ser. B (Statistical Methodology) (2017) doi:10.1111/rssb.12226.

See Also[bmt](#)**Examples**

```
library(fusionclust)
set.seed(42)
x<- c(rnorm(1000,-2,1), rnorm(1000,2,1))
out<- bmt(x)
k<- nclust(out)
```

Index

bmt, [2](#), [3](#), [5](#), [6](#)

cosci_is, [3](#), [4](#), [5](#)

cosci_is_select, [3](#), [4](#)

nclust, [2](#), [5](#)